

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A starting device for a single phase induction motor comprising:

a stator (B) having a running coil (B1) and a starting coil (B2);

a power source (F) which supplies current to said running coil (B1) and said starting coil (B2);

a running switch (S1) and a starting switch (S2), respectively connecting the running coil (B1) and the starting coil (B2) to the power source (F) when in a closed condition, said starting switch (S2) being conducted to an open condition upon completion of the motor start;

a current sensor (RS) connected in series between the power source (F) and the stator (B), in order to detect the current level supplied to the latter; and

a control unit (11) supplied by the power source (F) and receiving, from the current sensor (RS), signals representative of the current level being supplied to the stator (B), characterized in that wherein said control unit (11) is operatively connected to the running switch (S1) and to the starting switch (S2), in order to instruct the open and closed conditions thereof, the open condition of the starting switch (S2) being defined when the ratio (K) between the present current level (Ia) supplied to the stator (B) and informed by the current sensor (RS) to the control unit (11) and the starting current level (Ip) previously informed to said control unit (11) by the current sensor (RS) upon the

5. (Currently Amended) A starting device, according to claim 1, ~~characterized in that~~ wherein the current sensor (~~RS~~) is disposed in series between the power source (~~F~~) and the running switch (~~S1~~).

6. (Currently Amended) A starting device, according to claim 1, ~~characterized in that~~ wherein the current sensor (~~RS~~) is disposed in series between the power source (~~F~~) and the running and starting switches (~~S1 and S2~~).

7. (Currently Amended) A starting device, according to claim 1, ~~characterized in that it~~ includes further comprising:

a running capacitor (~~CR~~) disposed parallel to the running and starting switches (~~S1 and S2~~)
and

a starting capacitor (~~CS~~) disposed in series with the starting coil (~~B2~~).

8. (Currently Amended) A starting method for a single phase induction motor of the type comprising:

a stator (~~B~~) with a running coil (~~B1~~) and a starting coil (~~B2~~) for operating jointly with an AC power source (~~F~~) which supplies current to said running coil (~~B1~~) and said starting coil (~~B2~~);

a running switch (~~S1~~) and a starting switch (~~S2~~), respectively connecting the running coil (~~B1~~) and the starting coil (~~B2~~) to the power source (~~F~~) when in a closed condition, said starting

d—opening the starting switch (S2) when the ratio between the present current level (I_a) drawn by the stator (B) and the starting current level (I_p) reaches a value that is equal or inferior to a predetermined value (K_m).

detecting the voltage level in the power system in a first time interval (t_1), after the closing of the starting and running switches (S_1 and S_2), by a voltage sensor (SV) connected to the power

system, and informing said starting voltage level (V_p) to a control unit (11) supplied by the power source (F) and connected to the voltage sensor (SV) in order to receive, from the latter, information about the power system voltage;

detecting a present voltage level (V_a) of the power system during a second time interval (t_2) subsequent to the first time interval (t_1) after the closing of the starting and running switches (S1 and S2), and informing said present voltage level (V_a) to the control unit (11);

comparing the present voltage level (V_a) with that value of the starting voltage level (V_p);

calculating a value (K_m) as being equal to the product of a predefined reference value (K_r) multiplied by the ratio between the voltage read at the start moment, (V_p), and the present voltage (V_a) detected by the control unit; and

opening the starting switch (S2) when the ratio (K) between the present current level (I_a) drawn by the stator (B) and the starting current level (I_p) is greater than a value (K_m) after a maximum time interval previously defined for motor start completion has elapsed.

10. (Currently Amended) A starting method, according to claim 8, ~~characterized in that,~~
~~in wherein the step "b", the present current level of detecting a present current level~~ (I_a) drawn by the stator (B) is the one which supplies the running coil (B1) of the stator (B).

11. (Currently Amended) A starting method, according to claim 8, ~~characterized in that,~~
~~in wherein the step "b", the present current level of detecting a present current level~~ (I_a) drawn by

the stator (~~B~~) is the one which supplies current to the running coil (~~B1~~) and the starting coil (~~B2~~) of the stator (~~B~~).